

D-Link DEM-311GT Fiche technique



D-Link DEM-311GT 1000BASE-SX Multi-Mode 550 M LC SFP Transceiver

DEM-311GT

1000BASE-SX Multi-Mode 550 M LC SFP Transceiver

DEM-311GT

Industry-leading performance and affordability.

Features

- 850 nm multi-mode transceiver
- Maximum distance of up to 550 m
- Duplex LC connector
- MSA, RoHS-compliant
- Hot pluggable

High-Speed Network Transmission for Business Environments

D-Link's new line of Small Form-Factor Pluggables (SFPs) transceivers give you an industry-leading combination of performance and affordability. The DEM-311GT is a high-performance 850 nm multi-mode SFP transceiver supporting

Gigabit speeds on multi-mode fiber for distances of up to 550 m. The unit features a metal housing to reduce EMI and to increase durability.

Hot Pluggable

All D-Link transceivers are hot pluggable. You can connect a transceiver while the system is powered on without causing any issues, and easily swap one for another without having to reboot the switch each time. This permits modules to be added or removed without interrupting the network, facilitating maintenance and greatly reducing downtime.

Multiple Applications

Applications of the DEM-300 Series fiber transceivers include distributed multi-processing, Gigabit switch cascading, high-speed I/O file transfer, bus extension application, and channel extender/data storage. This versatility is invaluable for an expanding network, and helps the infrastructure grow with the business.

Small Form Pluggable (SFP) Package

The Gigabit SFP Transceivers use the Small Form-factor Pluggable (SFP) design. They provide the necessary signal amplification for data to be transmitted to the network cable from the port, and vice versa. The SFP form factor is advantageous because it is smaller than other form factors such as Xenpak, X2, and 10G XFP, ensuring lower costs, lower power disruption, and higher port density.

Specifications

- EMI: FCC Class B, ICES-003 Class B, CE Class B, VCCI Class B
- Safety: FDA/CDRH, TUV, cUL
- Hot Pluggable: Yes
- MSA Compliant: Yes
- RoHS Compliant: Yes
- Hardware version: F1
- Connector: Duplex LC Connector
- Single/bi Direction: single-direction
- Wavelength: 850 nm
- Output Optical Power (TX Optical Power): MAX.: -4 dBm
- Interface: MIN.: -17 dBm
- Input Optical Power (RX Optical Power): MAX.: -3 dBm
- Sensitivity: -17 dBm
- Cable Type: - multi-mode 50/125um fiber: reach 550m - multi-mode 62.5/125um fiber: reach 275m
- Power: 3.3V
- Max Input Current: 240mA
- Power Budget (MIN Power Budget): 7.5dB
- MAX Power Budget: 13dB
- Heat Generated: 1.54kJ/h
- Operation Temperature: 0-70°C
- Storage Temperature: -40-85°C
- Humidité (fonctionnement) : 10 % ~ 90 %
- Humidité (stockage) : 5 % ~ 90 %
- Dimension (L x P x H) : 13,4 mm x 56,4 mm x 10,35 mm
- Poids : 15,5g
- Vitesse : 1 Gbit/s
- Norme conforme : IEEE-802.3z 1000BASE-SX
- Type d'émetteur-récepteur : SFP
- Norme Fibre Channel FC-PI : 100-M5-SN-I et 100-M6-SN-I
- Prise en charge des médias fibre : multimode
- Distance : 550 M

[Acheter maintenant](#)